

Submit 5 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-26824

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Thomas AJJ Deep Com

8. Well No.

9. Pool name or Wildcat  
Wildcat Chester

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4<sup>th</sup> Street Artesia, NM 88210

4. Well Location

Unit Letter J : 1980 feet from the South line and 1980 feet from the East line

Section 8 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3546' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

8/20/02 – Squeeze Canyon perms with 30 bbls water, 25 bbls CACL<sub>2</sub> water, 5 bbls packer, 500 gals flow check, 10 bbls spacer, 150 sx Thixotropic cement 14.2#, 10 bbls spacer, 500 gals flow check, 10 bbls spacer, 100 sx Thixotropic cement 14.2# + 200 sx H Neat cement.

9/5/02 – Ran 44 joints 4-1/2" 11.6# P-110 (1903.46') casing set at 9350'. Float shoe set at 9350'. Float collar set at 9306'. Bottom marker set at 8786'. Cemented with 160 sx Super "C" Modified with additives (yld 1.61, wt 13.2). Install linger hanger. TIH with liner and cement with 160 sx Super "C" Modified. Top of liner at 7447'. Cement top approximately 7100'. PD at 10:30 PM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE September 19, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

OCT 08 2002

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of approval, if any: