

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

JUN 19 1992

O. C. D.
OFFICE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit K, 2080' FSL & 1980' FWL, Sec. 26-T20S-R24E, NMPM

5. Lease Designation and Serial No.

NM 045275

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Conoco AGK Fed. Com #6

9. API Well No.

30-015-26844

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole at 12:15 PM 6-4-92. Set 40' of 20" conductor. Notified Jim Amos with Carlsbad BLM of spud. Resumed drilling 14-3/4" hole at 4:00 PM 6-6-92. Ran 24 joints 9-5/8" 36# 8rd J-55 ST&C, casing set at 1070'. Regular guide shoe set 1070'. Insert float set 1024.69'. Cemented with 700 sacks Pacemaker Lite "C" + 1/2#/sx Celloseal + 10#/sx Gilsonite + 3% CaCl2 + 200 sacks "H" + 12% Thixadd, 1/2#/sx Flocele, 10#/sx Gilsonite and 3% CaCl2. Tailed in with 200 sacks "C" + 2% CaCl2 (yield 1.32, weight 14.8). PD 6:45 PM 6-7-92. Bumped plug to 600 psi, float held OK. Did not circulate cement. WOC. NOTE: Lost returns at 100'. Tagged cement on annulus at 110'. Redi-mix to surface with 6 yards redi-mix.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Supervisor

Date 6-9-92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: