

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

1992

O. C. D.  
OFFICE OF OIL & GAS

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☒ Other WORKOVER

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit K, 2080' FSL & 1980' FWL, Sec. 26-T20S-R24E, NMPM

5. Lease Designation and Serial No.

NM 045275

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Conoco AGK Fed. Com #6

9. API Well No.

30-015-26844

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Add perforations to existing Canyon Zone.

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water  
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-28-92. TOH w/pump, rods and tubing. Perforate Canyon 7687-7726' w/22 - .50" holes (2 SPF) as follows: 7687, 90, 92, 94, 96 and 7798' (2 SPF-12 holes); 7718, 20, 22, 24 and 7726' (2 SPF-10 holes). Straddled perfs 7718-26' and acidized w/1000g. 10% HCL. Straddled perfs 7687-7698' and acidized w/1000g. 20% HCL acid. Swabbed well.

10-30-92. RIH w/tubing, pump and rods. Returned well to production.

Perforations open: 7745-64'  
7718-26'  
7687-98'



14. I hereby certify that the foregoing is true and correct

Signature: *[Signature]*

Title: Production Supervisor

Date: 11-17-92

(This space for Federal or State office use)

Approved by:

Conditions of approval, if any:

Title:

Date: 11-17-92

1992