

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

+clsr
up

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAR 26 1992

WELL API NO. 30-015-26879
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG 9810
7. Lease Name or Unit Agreement Name Candelilla AKD State Com
8. Well No. 1
9. Pool name or Wildcat North Dagger Draw U/Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3619' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter 0 : 660 Feet From The South Line and 1650 Feet From The East Line Section 2 Township 20S Range 24E NMPM Eddy County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 8:00 AM 3-13-92. Set 40' of 20" conductor. Notified NMOC, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 12:00 AM 3-12-92. Ran 24 joints 9-5/8" 36# J-55 casing set 1068'. Guide shoe set 1068', insert float set 1023'. Cemented w/ 700 sx Lite "C" + 10% Gilsonite + 3% CaCl + 1/2# Flocele (yield 1.99, wt 12.7). Tail in w/200 sx Class "C" Neat + 2% CaCl (yield 1.32, wt 14.5). PD 3:00 PM 3-23-92. Bumped plug to 750 psi, held OK. Circulated 180 sacks cement. WOC. Drilled out 9:00 AM 3-24-92. WOC 18 hours. NU and tested to 1000 psi for 15 mins. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-25-92
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 30 1992