## Submit 3 Copies to D

## State of New Mexico

Form	C-103	
Revis	ed 1-1-	3

m C-103 ised 1-1-89	ì	Tc15
	ì	'c15

APR 2 3 1992

o Appropriate  Vistrict Office	Energy, Militals and Natur	ral Resources Department		Revised 1-1-89	
OISTRICT I O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2002 EIVED		WELL API NO.		
ISTRICT II	Santa Fe, New Mex		30-015-26914  5. Indicate Type of Lease		
O. Drawer DD, Artesia, NM 88210		APR 2 1 1992		TATE FEE X	
ISTRICT III 000 Rio Brazos Rd., Aztec, NM 87410		O. C. D.	6. State Oil & Gas Lease	No.	
SUNDRY NOT	ICES AND REPORTS ON	WELLS			
	OPOSALS TO DRILL OR TO DE RVOIR. USE "APPLICATION FO C-101) FOR SUCH PROPOSALS.	OR PERMIT"	7. Lease Name or Unit A	greement Name	
Type of Well: OIL GAS WELL X WELL	OTHER		Foster AN		
Name of Operator	DATTON /		8. Well No.		
YATES PETROLEUM CORPOR  Address of Operator	WITON		9. Pool name or Wildcat		
	ress of Operator South 4th St., Artesia, NM 88210		North Dagger D	raw U/Penn	
. Well Location					
Unit Letter A : 660	Feet From The North	Line and 660	Feet From The	East Line	
Section 1	Township 20S	Range 24F. whether DF, RKB, RT, GR, etc.)	NMPM Eddy	County	
	3582 G		· ///		
1. Check	Appropriate Box to Indi	cate Nature of Notice, I	Report, or Other Dat	a	
NOTICE OF IN	A A A		BSEQUENT REPO		
	TENTION TO.				
ERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTE	RING CASING	
EMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLIN		AND ABANDONMENT	
ULL OR ALTER CASING		CASING TEST AND	CEMENT JOB (A)		
THER:		OTHER:	•		
12. Describe Proposed or Completed Operatory) SEE RULE 1103.	erations (Clearly state all pertinent de	etails, and give pertinent dates, inc	cluding estimated date of starti	ng any proposed	
Spudded 26" hole 10: Resumed drilling 14- Guide shoe set 1068' Gilsonite + 1/2#/sx 2% CaCl2 (yield 1.32 OK. Circulated 180 to 8-3/4" and resume	3/4" hole 5:45 PM 4-, insert float set 1 Celloseal + 3% CaCl2 , wt 14.8). PD 10:0 sacks. WOC. Drille	-14-92. Ran 24 joi LO23'. Cemented w/ 2 (yield 1.94, wt 1 OO AM 4-16-92. Bun	ints 9-5/8" 36# J /900 sx PSL 65/35 L2.4). Tail in w nped plug to 1000	7-55 casing set 106 1/6% + 10#/sx 1/200 sx Class "C" 1 psi, float held	
I hereby certify that the information above is	true and complete to the best of my know	viedge and belief.	•		
I hereby certify that the information above is		viedge and belief. Production	Supervisor	DATE 4-20-92	

ORIGINAL SIGNED BY

APPROVED BY MINKE WILLIAMS
CONDITIONS OF APPROVAL, IF ANY: SUPERVISOR, DISTRICT II