Submit 3 Copies o Appropriate
District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89 \(\frac{1}{2}\)

MAY 2 0 1992

- DATE

DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION P.O. Box 2088	8	WELL API NO. 30-015-26919
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	87504 <b>2095 IVED</b>	5. Indicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410		MAY 1 4 1992 O. C. D.	STATE XX FEE 6. State Oil & Gas Lease No. LG 1525
( DO NOT USE THIS FORM FOR PRODIFFERENT RESE	ICES AND REPORTS ON WELLOPOSALS TO DRILL OR TO DEEPEN (RVOIR. USE "APPLICATION FOR PER 101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL GAS WELL XX WELL	OTHER		State CO Com
2. Name of Operator YATES PETROLEUM CORPOR	RATION		8. Well No.
3. Address of Operator			9. Pool name or Wildcat
105 South 4th St., Art	esia, NM 88210	· · · · · · · · · · · · · · · · · · ·	North Dagger Draw U/Penn
4. Well Location  Unit LetterB : _660  Section 36			Feet From The East Line  NMPM Eddy County
section 30	10. Elevation (Show whether I	DF, RKB, RT, GR, etc.)	
11. Check	Appropriate Box to Indicate N	Nature of Notice, R	eport, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	G OPNS. X PLUG AND ABANDONMENT
PULL OR ALTER CASING		CASING TEST AND CE	
OTHER:		)	Intermediate Casing X
work) SEE RULE 1103.  Spudded 26" hole 2:30 drilling with rotary joints 13-3/8" 54.5# 1.33, wt 14.6). Tail (yield 1.98, wt 12.4 5-8-92. WOC 18 hrs. 5-9-92. Ran 27 join set 1123'. Cemented wt 12.4). Tail in w Bumped plug to 500 p hrs and 45 mins. NU resumed drilling.	O PM 5-4-92. Set 40' of 14-3/4" hole 6:00 PM 5- J-55 casing set 170'. led in w/575 sx Class "C). PD 1:15 AM 6-8-92. Reduced hole to 12-1/4 ts 9-5/8" 36# J-55 casin w/700 sx PSL w/10#/sx C/ 200 sx Class "C" w/2% si. Circulated 170 sack	E 20" conductor5-92. TD surfa Cemented w/350 C" w/3% CaCl2, 1 Circulated 35 s 4" and resumed ong set 1167'. ( Gilsonite, 1/2#/ CaCl2 (yield 1 ks. WOC. Drill for 30 minutes	Cemented to surface. Resumed ace hole 4:00 PM 5-9-92. Ran 4 sx Class "C" w/2% CaCl2 (yield 10#/sx Gilsonite, 1/2# Celloseal. sacks. WOC. Drilled out 7:15 PM drilling. Guide shoe set 1167', insert float sx Celloseal w/3% CaCl2 (yield 1.98 .33, wt 14.6). PD 11:15 AM 5-9-92. led out 7:00 AM 5-10-92. WOC 17. Reduced hole to 8-3/4" and
I hereby certify that the information above is	true and complete to the best of my knowledge and	d belief.	
SIGNATURE LA CINILA	Dodlett 1	me Production S	Supervisor DATE 5-13-92
TYPEOGRAPHINT NAME Juani	ita Goodlett		<u>тегерноне но. 505/748-1</u> 47
(This space for State Use) ORI	GINAL SIGNED BY		6 3000

TITLE -

APPROVED BY -CONDITIONS OF APPROVAL, IF ANY:

MIKE WILLIAMS

SUPERVISOR, DISTRICT IT