

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY - 1 1992

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS O. C. D.**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit A, 860' FNL & 860' FEL, Sec. 19-T19S-R25E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross EG Federal Com #5

9. API Well No.

30-015-26937

10. Field and Pool, or Exploratory Area

North Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole 3:00 PM 4-10-92. Set 40' of 20" conductor. Cemented to surface. Resumed drilling 14-3/4" hole 3:00 PM 4-15-92. Lost returns at 479'. Mixed LCM. Regained 70% returns. TD 14-3/4" hole 4-16-92. Ran 26 joints 9-5/8" 36# casing set 1161'. Guide shoe set 1161', insert float set 1177'. Cemented w/1100 sx PSL "C" + 10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.98, wt 12.4). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.33, wt 14.8). PD 11:00 PM 4-16-92. Bumped plug to 1000 psi, float held OK. Circulated 125 sx cement. WOC. Drilled out 5:00 PM 4-17-92. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes. OK. Reduced hole to 8-3/4". NOTE: Witnessed by Don with BLM.

14. I hereby certify that the foregoing is true and correct

Signed Donna L. Sackett

Title Production Supervisor

Date 4-24-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side