

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

FEB 24 1992

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

O. C. D.  
ARTESIA OFFICE

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit C, 660' FNL & 1980' FWL, Sec. 20-T19S-R25E

5. Lease Designation and Serial No.

NM 0557142

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross EG Federal #6

9. API Well No.

30-015-26938

10. Field and Pool, or Exploratory Area

North Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole 9:35 AM 2-4-92 with rathole service. Notified Duncan Whitlock, BLM, Carlsbad, NM, of spud. Resumed drilling 14-3/4" hole 5:00 AM 2-5-92. Ran 25 joints 8-5/8" 36# J-55 casing set 1093'. Guide shoe set 1093', insert float set 1049'. Cemented w/200 sx "H" + 12% Thixad + 1% CaCl<sub>2</sub> + 15# Gilsonite (yield 1.56, wt 14.5), followed by 700 sx Lite "C" + 10#/sx Gilsonite + 3% CaCl<sub>2</sub> (yield 1.94, wt 12.4). Tailed in w/200 sx "C" + 2% CaCl<sub>2</sub> (yield 1.33, wt 14.8). PD 4:00 AM 2-7-92. Bump plug to 500 psi, float held OK. Cement did not circulate. WOC 4 hrs. Ran Temperature Survey and found TOC 110'. Ran 8 stages of 1". Cemented with 575 sx Class "C" + 4% CaCl. Circulated approximately 2 sacks cement. Drilled out 11:30 AM 2-8-92. WOC 31 hrs and 30 minutes. Reduced hole to 8-3/4" and resumed drilling.

14. I hereby certify that the foregoing is true and correct

*[Signature]*

Title Production Supervisor

Date 2-11-92

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

SJS

2 1992