

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

JUL - 1 1992

O. C. D.  
FEDERAL OFFICE

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
NM-0557142

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross EG Federal Com #8

9. API Well No.

30-015-26948

10. Field and Pool, or Exploratory Area

North Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit L, 1980' FSL & 660' FWL, Sec. 20-T19S-R25E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole 5:00 PM 6-5-92. Set 40' of 20" conductor pipe. Notified BLM, Carlsbad, NM, at spud time (answering service). Resumed drilling 14-3/4" hole 8:00 AM 6-9-92. TD 14-3/4" hole 2:15 PM 6-10-92. Ran 25 joints 9-5/8" 36# J-55 casing set 1124'. Guide shoe set 1124', insert float set 1079'. Cemented w/800 sx Lite Premium Plus w/10#/sx Gilsonite, 1/2#/sx Flocele, 3% CaCl2 (yield 1.84, wt 12.4). Tailed in w/200 sx Class "C" Neat w/2% CaCl2 (yield 1.36, wt 14.8). PD 8:50 PM 7-10-92. Bumped plug to 600 psi, float held OK. Circulated 234 sx to pit. WOC. Drilled out 3:00 PM 6-11-92. WOC 18 hrs and 10 minutes. NU and tested to 1000 psi for 15 minutes, OK. Reduced hole to 8-3/4" and resumed drilling.

6 1992  
SJS

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Production Supervisor

Date 6-17-92

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side