Form 3160-3 (November 1983) (formerly 9-331C)	DEPARTME	ITED STATES NT OF THE I OF LAND MANAG	NTEP	RIOR in the state	side)	5. LEASE DESIGNATION AND SEEIAL NO. NM-0557142			
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK						6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
1a. TYPE OF WORK		DEEPEN		PLUG BA	ск 🗆	7. UNIT AGREEMENT NAME			
b. TIPE OF WELL									
OIL WELL	GAS WELL OTHER		S. FABM OR LEASE NAME						
	oleum Corporatio	n				Ross "EG" Federal Com			
3. ADDRESS OF OPERA	TOR		9						
	Fourth Street, A					10. FIELD AND POOL, OR WILDCAT			
At surface				FEB 1 3 1992		N. Dagger Draw Upper Penr 11. SEC., T., B., M., OB BLK.			
1980 At proposed prod	'FSL and 660'F	L W. I		1 LD 1 0 1332		AND SURVEY OR AREA			
same		0010		O. C. D.		Sec. 19-T19S-R25E			
	ely 20 miles sou			et artenia, confic e		12. COUNTY OR PARISH 13. STATE			
15. DISTANCE FROM	PROPUSED). OF ACRES IN LEASE	17. NO. 0	Eddy NM			
LOCATION TO NE PROPERTY OR LE		660'			тотн	160			
18. DISTANCE FROM	FROPOSED LOCATION [*] LL, DRILLING, COMPLETED,		19. PH	ROPOSED DEPTH	20. ROTAF	20. ROTARY OR CABLE TOOLS			
OR APPLIED FOR, O	N THIS LEASE, FT.	<u></u>	8	300'	Rot	ary			
-	w whether DF, RT, GR, etc.))				22. APPROX. DATE WORK WILL START* ASAP			
<u></u>	571'	PROBOSED CAS		CEMENTING PROGRA					
		WEIGHT PER F			1M				
14 3/4"	SIZE OF CASING	<u>36# J-55</u>		SETTING DEPTH	- 1100 s	QUANTITY OF CEMENT Sacks (<u>circulated</u>)			
8 3/4"		23-26#		TD		ranted (600' above Wolfcomp)			
		J-55 & N-	80		+				
formations	5. Approximately ² f gravel and cav will perforate a <u>AM:</u> FW gel/LCM t	1100' of su ings. If co nd stimulate to 1100'; FW dril will be	rface mmerc as n to 50 inst	casing will b ial, productio eeded for prod 000'; cut Brine	e set ar n casing uction. to 2700	n and intermediate nd cement circulated g will be run and D'; SW gel/Starch to TD. and tested daily. KELLIVED JAN28 1992			
IN ADOVE SPACE DES zone. If proposal i preventer program, 24. BIGNED	CRIBE PROFOSED PROGRAM: s to drill or deepen directi if any.	\mathbb{N}	pen or p t data c 	blug back, give data on on subsurface locations a Landman	present produ	DATE			
(This space for	Federal or State office use)								
PERMIT NO		<u> </u>		APPROVAL DATE		·			
				a de Madracia		DATE 2-12-92			
APPROVED BY		<u></u> TI	TLE	CARLERAD MERICE	AREA	DATE OF 10 1-			
	UIREMENTS AND	*See Instru	uctions	On Reverse Side					

ATTACHED Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Submit to Appropriate District Office State Lease - 4 copies Fee Lease - 3 copies

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Antesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL LOCATION AND ACREAGE DEDICATION PLAT

All Distances must be from the outer boundaries of the section

perator				Lease	······			Well No.	
•	PETROLEUM C	ORPORATION		RO	SS EG FEDEH	RAL COM		9	
nit Letter	Section	Township		Range	<u>_</u>	·	County		
I	19	19	SOUTH	25	EAST	NMPM	EDDY	COUNTY, NM	
ctual Footage Loca	tion of Well:	• <i>*</i>							
1980	feet from the	SOUTH	line and	660		feet from	the EAST	line	
round level Elev.	Produci	ng Formation		Pool		•	٨	Dedicated Acreage:	
3571.	دز)	co Canya	~	North	Dayler Dr.	m Unor	Penn	60 Acr	es
2. If more	the acreage dedicate than one lease is de than one lease of di	dicated to the well,	outline each and	identify the ov	mership thereof (bo	oth as to worki			
If answer this form	ion, force-pooling, e Yes [is "no" list the owned if neccessary.	No If an ins and tract descrip		actually been	consolidated. (Use			ag or otherwise)	
No allowa	able will be assigned non-standard unit, el	to the well until all liminating such inte	i interests have b rest, has been an	een consolidate proved by the I	a (oy communitiza Division.	uon, uniuzauoi	i, torcea-poolii	ug, or outerwise)	
							I hereby contained here best of my know Signature Printed Name Ken Bear Position Landman Company YATES PE Date January	TROLEUM CORPOR	ormat le to
			50			12	on this plat actual surve supervison, a correct to t belief. Date Surveye JANUARY	TTO DE TICO	note under true
				000 1500		£E	REG. ST. Centroceta N NM PESP	5412 E	

YATES PETROLEUM CORPORATION

Ross "EG" Federal #9 1980' FSL and 660' FEL Section 19-T19S-R25E Eddy County, New Mexico

In conjunction with Form 3160-3, Application for Permit to Drill subject well, Yates Petroleum Corporation submits the following ten items of pertinent information in accordance with BLM requirements.

- 1. The geological surface formation is Caliche:
- 2. The estimated tops of geologic markers are as follows:

San Andres	691'
Glorieta	2,173'
Bone Spring Lime	3,587'
Wolfcamp Lime	5,494'
Canyon Lime	7,612'
Canyon Dolomite top	7,747'
Base Canyon Dolomite	7,979'
TD	8,300'

3. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Water:Approximately 275'Oil or Gas:Canyon

- 4: Proposed Casing Program: See Form 3160-3.
- 5. Pressure Control Equipment: See Form 3160-3 and Exhibit B.
- 6. Mud Program: See Form 3160-3.
- 7. Auxiliary Equipment: Kelly Cock; pit level indicators and flow sensor equipment; sub with full-opening valve on floor, drill pipe connections.
- 8. Testing, Logging and Coring Program:

Samples: 10' samples from surface depth to total depth.

DST's: As warranted.

Coring: As warranted.

Logging: CNL-LDT from TD to casing, with GR-CNL up to surface; DLL with RxO from TD to casing.

- 9. No abnormal pressures or temperatures are anticipated.
- 10. Anticipated starting date: As soon as possible after approval.

MULTI-POINT SURFACE USE AND OPERATIONS PLAN Yates Petroleum Corporation Ross "EG" Federal #9 1980' FSL and 660' FEL Section 19-T19S-R25E Eddy County, New Mexico

This plan is submitted with Form 3160-3, Application for Permit to Drill, covering the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operations plan, the magnitude of the surface disturbance involved and the procedures to be followed in rehabilitating the surface after completion of the operations, so that a complete appraisal can be made of the environmental effect associated with the operations.

1. EXISTING ROADS:

Exhibit A is a portion of BLM map showing the well and roads in the vicinity of the proposed location. The proposed wellsite is located approximately 20 miles southwest of Artesia, New Mexico, and the access route to the location is indicated in red and green on Exhibit A.

DIRECTIONS:

- 1. Go south of Artesia on Highway 285 for approximately 13 miles to Rockin R Red Road.
- 2. Turn west and go approximately 6.5 miles.
- 3. Turn on lease road going south for .2 miles, turn west and follow lease road for approximately .8 miles.
- 4. New road starts here.

2. PLANNED ACCESS ROAD

- A. The proposed new access will be approximately 1000' in length from point of origin to the southeast edge of drilling pad. The road will lie in an east to west direction.
- B. The new road will be 14 feet in width (driving surface) and will be adequately drained to control runoff and soil erosion.
- C. The new road will be bladed with drainage on one side. No traffic turnout will be built.

3. LOCATION OF EXISTING WELL

- A. There is drilling activity within a one-mile radius of the wellsite.
- B. Exhibit D shows existing wells within a one-mile radius of the proposed wellsite.

4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES

- A. There are production facilities on this lease at the present time.
- B. In the event that the well is productive, the necessary production facilities will be installed on the drilling pad. If the well is productive oil, a gas or diesel self-contained unit will be used to provide the necessary power. No power will be required if the well is productive of gas.

5. LOCATION AND TYPE OF WATER SUPPLY:

- A. It is planned to drill the proposed well with a fresh water system. The water will be obtained from commercial sources and will be hauled to the location by truck over the existing and proposed roads shown in Exhibit A.
- 6. SOURCE OF CONSTRUCTION MATERIALS:

Federal pit located in Section 21-T19S-R25E.

Ross "EG" Federal #9 Page 2

7. METHODS OF HANDLING WASTE DISPOSAL:

- A. Drill cuttings will be disposed of in the reserve pits.
- B. Drilling fluids will be allows to evaporate in the reserve pits until the pits are dry.
- C. Water produced during operations will be collected in tanks until hauled to an approved disposal system, or separate disposal application will be submitted.
- D. Oil produced during operations will be stored in tanks until sold.
- E. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- F. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.
 G. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling
 - and/or completion operations.

8. ANCILLARY FACILITIES: As per NTL 92-I effective 2/1/92, trash can no longer be buried on location.

A. A 3" steel pipeline, 30' wide, buried to the Parish IV #1 Battery. (On topo)

9. WELLSITE LAYOUT:

- A. Exhibit C shows the relative location and dimensions of the well pad, the reserve pits, the location of the drilling equipment, rig orientation and access road approach. A cross section of a drill pad with approximate cuts, fills and pad orientation is shown on Exhibit E.
- B. The reserve pits will be plastic lined.
- C. A 400' x 400' area has been staked and flagged.
- 10. PLANS FOR RESTORATION
 - A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing a condition as possible.
 - B. Unguarded pits, if any, containing fluids will be fenced until they have dried and been levelled.
 - C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the landowner agreement will be complied with and will be accomplished as expeditiously as possible. All pits will be filled level within 90 days after abandonment.
- 11. SURFACE OWNERSHIP: Mr. Carl Ross Yates Petroleum Corporation and Mr. Ross have made an agreement on surface damages..

12. OTHER INFORMATION:

- A. Topography: Refer to the existing archaeological report for a description of the topography, flora, fauna, soil characteristics, dwellings, historical and cultural sites.
- B. The primary surface use is for grazing.

Ross "EG" Federal #9 Page 3

13. OPERATOR'S REPRESENTATIVE

A. Thro'ugh A.P.D. Approval:

Ken Beardemphl, Landman Yates Petroleum Corporation 105 South Fourth Street Artesia, New Mexico 88210 Phone (505) 748-1471 B. Through Drilling Operations, Completions and Production:

> Mike Slater, Operations Manager Yates Petroleum Corporation 105 South Fourth Street Artesia, New Mexico 88210 Phone (505) 748-1471

14. CERTIFICATION:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route, that I am familiar with the conditions which presently exist; that the statements made in this plan are to the best of my knowledge, true and correct; and , that the work associated with the operations proposed herein will be performed by Yates Petroleum Corporation and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

1-27-92

Date

Ken Beardemph

Landman





THE FOLLOWING CONSTITUTE MINIMUM BLOWOUT PREVENTER REQUIREMENTS

- All preventers to be hydraulically operated with secondary manual (1. installed prior to drilling out from under casing.
- Choke outlet to be a minimum of 3 " diameter. 2.
- 3.
- Kill line to be of all steel construction of 2" minimum diameter. All connections from operating manifolds to preventers to be all st 4. hole or tube a minimum of one inch in diameter.
- The available closing pressure shall be at least 15% in excess of t 5. . required with sufficient volume to operate the B.O.P.'s.
- All connections to and from preventer to have a pressure rating equ 6. to that of the B.O.P.'s.
- 7. Inside blowout preventer to be available on rig floor.
- Operating controls located a safe distance from the rig floor Hole must be kept filled on trips below intermediate casing. 9.

Exhibit B

YATES PETROLEUM CORPORATION



Exhibit C

