

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

NOT - 9 1992

**O. C. D.
ARTESIA OFFICE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit P, 660' FSL & 860' FEL, Sec. 26-T20S-R24E

5. Lease Designation and Serial No.

NM 045275

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Conoco AGK Federal #9

9. API Well No.

30-015-26952

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Surface Casing
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole 11:00 PM 9-18-92 with Auger Air. Set 80' of 20" conductor, redi-mix to surface. Notified BLM Answering Service, Carlsbad, NM, of spud. Resumed drilling 14-3/4" hole 2:30PM 9-21-92. Ran 25 joints 9-5/8" 36# J-55 casing st 1108'. Guide shoe set 1108', insert float set 1063'. Cemented w/900 sx Premium Plus H/L with 10#/sx Gilsonite, 1/2#/sx Flocele + 3% CaCl2 (yield 1.99, wt 12.4). Tail in w/200 sx Class "C" Neat with 2% CaCl2 (yield 1.32, wt 14.8). PD 3:05 PM 7-22-92. Bump plug to 600 psi, float held OK. Cement did not circulate. WOC 4 hrs. Ran Temperature Survey and found TOC at 0. Ran 4 stages of 1". Cemented w/275 sx Class "C" with 3% CaCl2. Circulated 10 sacks cement to surface on last stage. PD 11:05 PM 9-22-92 on 4th stage. WOC. Drilled out 9:00 AM 9-23-92. WOC 18 hrs. Reduced hole to 8-3/4" and resumed drilling.

14. I hereby certify that the foregoing is true and correct

[Signature]

Title Production Supervisor

Date 9-24-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date