

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator YATES PETROLEUM CORP.		Lease Candlelilla AKD St Com		Well # 2	
Location of Well	Unit N	Section 2	Township 20	Range 24	County Eddy
Drilling Contractor	Undesignated		Type of Equipment Rotary		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 3/4"	* 9 5/8"	36# J-55		1100'	1100 Circ
8 3/4"	7"	23# & 26#		8100' TD	As Warranted

Casing Data:

Surface _____ joints of 9 5/8" inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date 5-6-92

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1074' Set 1074' Feet of 9 5/8" Inch 36 # Grade J-55(New) used csg. @ 1074' with _____ sacks neat cement around shoe+ 900 sax Hall. Lite additives 10 # gilsonite, 1/4 # floredl, 370 ccPlug down @ 1:45 (AM) (PM) Date 5-10-92Cement circulated yes No. of Sacks 210 crCemented by Halliburton Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

Lost circ @ 260'

Last drlg break @ 282'