

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-26976
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Binger AKU
8. Well No. 1
9. Pool name or Wildcat North Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3552' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter B : 660 Feet From The North Line and 1980 Feet From The East Line Section 29 Township 19S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, Resume drilling & surface casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole at 8:30 AM 6-26-93. Set 40' of 20" conductor pipe. Cemented to surface. Resumed drilling with rotary tools (14-3/4" hole) at 7:15 AM 7-2-93.

TD 1163'. Ran 26 joints of 9-5/8" 36# J-55 (1167.11') of casing set at 1163'. 1-Texas Pattern notched guide shoe set at 1163'. Insert float set at 1118.45'. Cemented with 200 sacks "H", 12% Thixad, 10#/sack gilsonite and 2% CaCl2 (yield 1.55, weight 14.6) and 900 sacks Pacesetter Lite "C", 10#/sack gilsonite, 1/2#/sack celloseal and 3% CaCl2 (yield 1.94, weight 12.4). Tailed in with 200 sacks Class "C" Neat 2% CaCl2 (yield 1.32, weight 14.8). PD 10:50 PM 7-3-93. Bumped plug to 600 psi, OK. Circulated 195 sacks to pit. WOC. Drilled out at 4:45 PM 7-4-93. WOC 17 hours and 55 minutes. Nippled up and tested to 1000# for 15 minutes, OK. Cut off and welded on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 7, 1993
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT I

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUL 20 1993