

+ 158 UP

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-26977
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Roy AET
8. Well No. 4
9. Pool name or Wildcat North Dagger Draw U/Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line Section 8 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3545' GR
--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 1:15 PM 5-19-92. Set 40' of 20" conductor. Redi-Mix to surface. Notified NMOCD, Artesia, NM of spud. Ran 24 joints 9-5/8" 36# casing set 1075'. Guide shoe set 1075'. Insert float set 1031'. Cemented w/800 sx PSL "C" w/10#/sx Gilsonite, 1/2#/sx Cello-seal, 3% CaCl2 (yield 1.98, wt 12.4). Tail in w/200 sx Class "C" w/2% CaCl (yield 1.33, wt 14.6). PD 4:15 PM 5-22-92. Bumped plug to 500 psi, float held OK. Circulated 138 sacks. WOC. Drilled out 10:45 AM 5-23-92. WOC 18 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes. Reduced hole to 8-3/4" and resumed drilling. Witnessed by NMOCD, Artesia, NM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 5-28-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR DISTRICT II

APPROVED BY _____ DATE JUN 3 1992

CONDITIONS OF APPROVAL, IF ANY: