

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

JUN 29 1992

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 82641 862-41

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hill View AHE Fed. Com #12

9. API Well No.

30-015-26983

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

SUNDRY NOTICES AND REPORTS ON WELLS O. C. D.

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit I, 1980' FSL, 660' FEL, Sec. 23-T20S-R24E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Run Surface Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 10:00 AM 5-15-92. Set 40' of 20" conductor. Notified BLM, Carlsbad, NM, of spud. Resumed drilling 14-3/4" hole 7:00 AM 5-17-92. Ran 24 joints 36# J-55 casing set 1058'. Guide shoe set 1058', insert float set 1013'. Cmt'd w/800 sx Lite "C" w/10#/sx Gilsonite, 1/2#/sx Flocele, 3% CaCl2 (yield 1.97, wt 12.7). Tail in w/200 sx Premium Plus w/2% CaCl2 (yield 1.32, wt 14.8). PD 6:15 PM 5-20-92. Bumped plug to 575 psi, float held OK. Circulated 165 sacks. WOC. Drilled out 12:15 PM 5-21-92. WOC 18 hrs. NU and tested to 1000 psi for 15 minutes, OK. Reduced hole to 8-3/4", resumed drilling.

ALL FOR RECORD

ABZ

JUN 14 1992

NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed

[Signature]

Title Production Supervisor

Date 6-15-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date