## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Mi als and Natural Resources Department

Form	C	-10	3
Revis	ed	1-1	ŀ

Form	C	-10	03
Revis	ed	1.	1-89

DISTRICT I		
P.O. Box 1980	, Hobbs, NM	88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

<b>)</b> [[	CONSERVATION DIVISION	
	P.O. Box 2088	

Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-26990 5. Indicate Type of Lease FEE XX **STATE** 

1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) RECEIVED 1. Type of Well: Dahlia ALA Com GAS WELL WELL XX 8. Well No. 2. Name of Operator YATES PETROLEUM CORPORATION <del>. c. b.</del> 9. Pool name or Wildcat 3. Address of Operator CONTROL MERICE 105 South 4th St., Artesia, NM 88210 South Dagger Draw U/Penn 4. Well Location . 1980 Feet From The South 660 Feet From The West L Line and Line Unit Letter . 25 20S 24E Eddy Range Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3614' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING CASING PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CHANGE PLANS TEMPORARILY ABANDON CASING TEST AND CEMENT JOB X PULL OR ALTER CASING OTHER:\_ OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spudded 26" hole 5-1-92. Set 80' of 20" conductor pipe. Notified Mike Williams, NMOCD, Artesia, NM of spud. Resumed drilling 14-3/4" hole 5-3-92. TD'd hole 3:45 PM 5-4-93.

Ran 25 joints 9-5/8" 36# J-55 casing set 1094'. Guide shoe set 1094'. Insert float set 1052'. Cemented w/200 sx Class "H"+ 12% Thikset + 10%/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.73, wt 14.0) and 900 sx PSL "C" (65-35-6) + 10%/sx Gilsonite + 1/2%/sx Celloseal + 3% CaCl2 (yield 2.16, wt 12.17). Tailed in w/200 sx Class "C" Neat and 2%CaCl2 (yield 1.34, wt 14.8). PD 12:20 AM 5-5-92. Bumped plug to 800 psi, float held OK. Cement did not circulate. WOC 4 hours. Ran temperature survey and found TOC at 90'. Ran 1". Tag cement at 90'. Spotted 200 sx Class "C" Neat + 2% CaCl2. PD 8:00 AM 5-5-92. Circulate cement on 1st stage of 1". WOC. Drilled out at 6:20 PM 5-5-92. WOC 18 hours. NU and tested to 1000 psi for 15 minutes. Reduced hole to 8-3/4" and resumed drilling.

			······································
	mation above is true and complete to the best of my know		
SIGNATURE	neta Doodlett	mme Production Supervisor	DATE5-6-92
TYPE OF PRINT NAME	Juanita Goodlett		те <b>лерно</b> ме мо. 505/748 <b>–</b> 1471
(This space for State Use)	ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR DISTRICT IF		MAY 1 1 1992

CONDITIONS OF APPROVAL, IF ANY: