Submit 3 Copies to Appropriate District Office

Energy, Mine

1	tate	10	New.	Mexico	
	and	N	atural	Resources	Departmen

Form	C-103
Revis	ed 1-1-89

DISTRICT I			
P.O. Box 1980.	Hobbs.	NM	88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

IL	CC)NS	EK	VA	$\Gamma\Gamma$	UN.	(D	IV.	121	Uľ
			PC) R	× 2	ጸጸበ				

Santa Fe, New Mexico 87504-2088

WELL API NO.			
30-015-269	90		
5. Indicate Type of Le	STATE	•	FEE XX

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE 'APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS) 1. Type of Well: ONE	000 Rio Brazos Rd., Aztec, NM 87410	
DIFFERENT RESPONDENCE TO FOR SUCH PROPOSALS) Type of Well: OR WILL WILL WILL WILL WILL WILL WILL WIL	SUNDRY NOTICES AND REPORTS ON WELLS	
Name of Operator O. C. D. O. C. D. Name of Operator O. C. D. O. C	DIFFERENT RESERVOIR, USE APPLICATION FOR PERMIT	7. Lease Name or Unit Agreement Name
Name of Operator YATES PETROLEUM CORPORATION MAY 2 2 1992 8. Well No. 1 Address of Operator 105 South 4th St., Artesia, NM 88210 O.C.D. 19. Pool name or Wildcat South Dagger Draw U/Penn Well Location Unit Letter L: 1980 Feet From The South Line and 660 Feet From The West Line Section 25 Township 20S Range 24E NMPM Eddy County 10. Elevation (Show whether Dr. RKB, RT, GR, etc.) 3614' GR NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Set 7" 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMMI, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circul	WELL XX WELL OTHER	Dahlia ALA Com
105 South 4th St., Artesia, NM 88210 Unit Letter L 1980 Feet From The South Line and 660 Feet From The West Line	Name of Operator / MAY 2 2, 1992	1
Well Location Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line Section 25 Township 20S Range 24E NMFM Eddy County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3614' GR 1. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB ULL OR ALTER CASING OTHER: Set 7" 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSI. "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and 4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. Wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. Wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. Wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 1.18. Wt	Address of Operator 105 South 4th St., Artesia, NM 88210	l l
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3614' GR 10. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	Well I cration	Feet From The West Line
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING OTHER: CASING TEST AND CEMENT JOB OTHER: Set 7" 12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMV1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulate 126 mins. Circulate 127 mins. Circulate 128 mins. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18. wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulate 150 mins.	Section 25 Township 20S Range 24E	NMPM Eddy County
NOTICE OF INTENTION TO: ERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CHANGE PLANS CASING TEST AND CEMENT JOB CHANGE Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulate	//////////////////////////////////////	
ERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: OTHER: Set 7"		Report, or Other Data
EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: OTHER: OTHER: TO SET 7" OTHER: Set 7" OTHER: TO SITURE Not a starting any proposed work) SEE RULE 1103. TO 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 128 wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 128 wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated 128 wt 15.6).	NOTICE OF INTERNIOR TO:	
CASING TEST AND CEMENT JOB OTHER: OT	ENFORM REMEDIAL WORK	
OTHER: Set 7" 12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulate	EMPORALIE / NEW SOL	
DTHER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulated	OLL ON ALIEN OADING	
work) SEE RULE 1103. TD 8170'. Reached TD 5-17-92. Ran 198 joints 7" 23# and 26# J-55 and N-80 casing set at 8170'. Float shoe set 8170', float collar set 8124'. DV tool set 5565'. Cmt'd in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulate	THER: OTHER:	/" <u>K</u>
at 8170'. Float shoe set 8170', float collar set 8124'. By tool set 3303'. Gilt d'in 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 600 sx "H" w/5# CSE, 5# Gilsonite, 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 AM 5-19-92. Bumped plug to 2100 psi for 3 mins. Circulated 128 sacks. Circulate thru DV tool 3 hrs. Stage 2: 650 sx PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF-14. Tail in w/100 sx "H" Neat (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plug to 3400 psi for 3 mins. Circulate	work) SEE RULE 1103.	
	at 8170'. Float shoe set 8170', float collar set 8124. 2 stages. Stage 1: 500 gals WMW1, 500 gals Surebond + 6 1/4# Flocele, .65% CF-14 (yield 1.32, wt 15.1). PD 7:00 psi for 3 mins. Circulated 128 sacks. Circulate thru D PSL "C" w/1/4# Flocele, 5# Gilsonite, 5# Salt and .4% CF (yield 1.18, wt 15.6). PD 11:15 AM 5-19-92. Bumped plu	OO sx "H" w/5# CSE, 5# Gilsonite, AM 5-19-92. Bumped plug to 2100 V tool 3 hrs. Stage 2: 650 sx -14. Tail in w/100 sx "H" Neat g to 3400 psi for 3 mins. Circul
		·

ORIGINAL SIGNED BY (This space for State Use)

MIKE WILLIAMS

Juanita Goodlett

MAY 2 5 1992

TELEPHONE NO. 505/748-1471

CONDITIONS OF APPROVAL, IF ANY:

TYPE OR PRINT NAME

APPROVED BY-