

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

AUG 14 1992

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G, 1980' FNL, 1980' FEL, Sec. 20-T19S-R25E

5. Lease Designation and Serial No.

NM 0557142

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross EG Federal Com #10

9. API Well No.

30-015-26997

10. Field and Pool, or Exploratory Area

North Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 9:30 AM with rathole. Set 40' of 20" conductor. Notified BLM, Carlsbad, NM at spud time. Resumed drilling 14-3/4" hole 7:15 AM 7-29-92. Lost returns at 832'. Mix LCM pills and pumped. Washed 50' to bottom, no fill. TD 14-3/4" hole 1:30 PM 7-30-92. Ran 26 jts 9-5/8" 36# 8rd J-55 ST&C casing set 1145'. Guide shoe set 1145', insert float set 1100'. Cmt'd w/200 sx "H" w/12% Thixad, 1/2#/sx Flocele, 10#/sx Gilsonite w/2% CaCl2 (yield 1.56, wt 14.5). Tailed in w/700 sx PSL "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 11:00 PM 7-30-92. Bumped plug to 500 psi, released pressure and float held OK. Cement did not circulate. WOC 3 hrs. Ran 10 stages of 1". Cemented w/795 sx Class "C" w/4% CaCl2. On last stage of 1", tagged cement 10'. PD 6:45 PM 8-1-92. Circulated 10 sacks. WOC. Drilled out 3:30 AM 8-2-92. WOC 52 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed James A. Dordick

Title Production Supervisor

Date 8-3-92

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side