

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N, 660' FSL & 1980' FWL, Sec. 14-T20S-R24E

5. Lease Designation and Serial No.

NM 42787-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Senita AIP Fed. Com #2

9. API Well No.

30-015-27013

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☒ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 2:00 PM 10-27-92. Set 40' of 20" conductor and cemented to surface. Notified BLM, Carlsbad, NM, of spud. Resumed drilling 14-3/4" hole 5:00 PM 10-31-92. Lost returns at 184'. Pumped LCM with no returns. Dry drilling. Ran 24 joints 9-5/8" 36# J-55 casing, set 1071'. Guide shoe set 1071', insert float set 1026'. Cemented w/900 sx Lite "C" + 1/2#/sx Flocele + 10#/sx Gilsonite + 3% CaCl2 (yield 1.89, wt 12.6). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 11:07 PM 11-2-92. Bumped plug to 600 psi, float held OK. Cement did not circulate. WOC 4 hrs. Ran Temperature Survey and found TOC at 105'. Ran 1". Tag cement 150'. Spotted 250 sx "C" + 3% CaCl2. Circulated cement to surface. PD 8:30 AM 11-3-92. WOC. Drilled out 1:45 AM 11-4-92. WOC 26 hrs and 38 mins. Reduced hole to 8-3/4" and resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signature *Senita Doodlett*

Title Production Supervisor

Date 11-9-92

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side