

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-015-27027

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

John AGU

8. Well No.

6

9. Pool name or Wildcat

South Dagger Draw U/Penn

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter B : 7100 Feet From The North Line and 1980 Feet From The East Line

Section 14 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3616' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 4:30 PM 1-4-93. Set 40' of 20" conductor and redi-mix to surface. Resumed drilling 14-3/4" hole 1-6-93. Ran 24 joints 9-5/8" 36# J-55 casing set at 1075'. Guide shoe set 1075', insert float set 1030'. Cemented w/200 sx Class "H" w/12% Thixad + 10# Gilsonite + 2% CaCl2 + 1/2# Celloseal (yield 1.55, wt 14.6), and 900 sx PSL "C" + 10# Gilsonite + 3% CaCl2 + 1/2# Celloseal (yield 1.94, wt 12.4). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 10:45 PM 1-7-93. Bumped plug to 900 psi, float held OK. Cement did not circulate. Tagged cement 90' down. Poured 8-1/2 yards of redi-mix and got cement to surface. WOC. Drilled out 4:30 PM 1-8-93. WOC 17 hours and 45 minutes. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett

TITLE Production Supervisor

DATE 1-13-93

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 18 1993