

+clst
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87508

FEB 15 1993

O. C. D.

WELL API NO. 30-015-27040
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-2781
7. Lease Name or Unit Agreement Name State CO Com
8. Well No. 8
9. Pool name or Wildcat North Dagger Draw U/Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter C : 9160 Feet From The North Line and 1980 Feet From The West Line Section 36 Township 19S Range 24E NMPM Eddy County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3606' GR
---	--	--	--	--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Spudded 26" hole 11:05 AM 1-25-93. Set 40' of 20" conductor pipe. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 1-27-93. Lost returns 456'. Drilling with no returns. Ran 24 joints 9-5/8" 36# J-55 casing set 1078'. Guide shoe set 1078', insert float set 1033'. Cemented w/200 sx "H" w/12% Thixad, 10#/sx Gilsonite, 1/2/sx Celloseal, 2% CaCl2 (yield 1.55, wt 14.6), and 900 sx PSL "C" w/10#/sx Gilsonite, 1/2#/sx Celloseal, 3% CaCl2 (yield 2.16, wt 12.2). Tail in w/200 sx Class "C" Neat w/2% CaCl2 (yield 1.32, wt 14.8) PD 11:05 PM 1-28-93. Bump plug to 400 psi, held OK. Circulated 190 sacks to pit. WOC. Drilled out 5:00 PM 1-29-93. WOC 18 hours. NU and tested to 1000 psi for 15 minutes, OK. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-11-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE FEB 15 1993

CONDITIONS OF APPROVAL, IF ANY: