

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

SEP 29 1993

5. Lease Designation and Serial No.

NM-0557142

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross EG Federal Com #12

9. API Well No.

30-015-27052

10. Field and Pool, or Exploratory Area

North Dagger Draw Upper

11. County or Parish, State

Eddy County, New Mexico

2. Name of Operator
YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL (Unit H) of Section 19-T19S-R25E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, surface csg & cmt
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 26" hole at 5:30 PM 7-27-93. Set 40' of 20" conductor casing. Cement to surface.
NOTE: Notified BLM of spud time. Resumed drilling with rotary tools (14-3/4" hole) at 9:00 AM 7-30-93.

TD 1077'. Ran 24 joints of 9-5/8" 36# (1080.62') of casing set at 1077'. 1-Texas Pattern notched guide shoe set at 1077'. Insert float set at 1032'. Cemented with 200 sacks Premium Plus, 12% Thixad and 2% CaCl₂ (yield 1.51, weight 14.0) and 900 sacks Halliburton Lite, 10#/sack gilsonite, 1/4#/sack flocele and 2% CaCl₂ (yield 1.81, weight 14.8). Tailed in with 200 sacks Class "C" Neat 2% CaCl₂ (yield 1.32, weight 14.8). PD 6:16 AM 8-1-93. Bumped plug to 600 psi, OK. Circulated 205 sacks. WOC. Drilled out at 12:15 AM 8-2-93. WOC 18 hours. Nippled up and tested to 1000# for 15 minutes, OK. Cut off and welded on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date August 26, 1993

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side