

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
AUG 12 1992

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS **Q.C.D.**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit J, 1980' FSL & 1980' FEL, Sec. 26-T20S-R24E

5. Lease Designation and Serial No.

NM 045275

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Conoco AGK Federal #11

9. API Well No.

30-015-27054

10. Field and Pool, or Exploratory Area

South Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 9:30 AM 7-19-92 with Auger Air. Set 80' of 20" conductor pipe. Notified Cathy Queen, BLM, Carlsbad, NM, of spud.
Resumed drilling 14-3/4" hole 7:00 AM 7-22-92. Ran 24 joints 9-5/8" 36# J-55 casing set at 1074'. Guide shoe set 1074'. Insert float set 1030'. Cemented w/900 sx Lite + 10# Gilsonite + 3% CaCl₂ + 1/2# Flocele (yield 1.99, wt 12.4). Tailed in w/200 sx Premium Plus "C" + 3% CaCl₂ (yield 1.32, wt 14.8). PD 2:30 AM 7-24-92. Bumped plug to 500 psi, float held OK. Circulated 5 sacks cement. WOC.
Drilled out 8:30 PM 7-24-92. WOC 18 hours. Reduced hole to 8-3/4" and resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

(This space for Federal or State office use)

Title Production Supervisor

Date 7-27-92

Approved by

Conditions of approval, if any:

Title

Date