RECEIVEC

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SEP 0 2 1992

O. C. D.

FORM APPROVED
Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

NM 045275

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. XX Oil Gas Well Other 2. Name of Operator Conoco AGK Federal #12 (505) 748-1471)9. API Well No. YATES PETROLEUM CORPORATION 3. Address and Telephone No. 30-015-27076 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 North Dagger Draw U/Penn 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit E, 1980' FNL & 660' FWL, Sec. 11-T20S-R24E Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment **New Construction** Recompletion Non-Routine Fracturing Subsequent Report Plugging Back Casing Repair Water Shut-Off Altering Casing Conversion to Injection Final Abandonment Notice Other Surface Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 26" hole 7:15 PM 8-11-92. Set 40' of 20" conductor. Notified BLM, Carlsbad, NM of spud. Resumed drilling 14-3/4" hole 6:00 AM 8-13-92. Ran 24 joints 9-5/8" 36# J-55 casing set 1071'. Guide shoe set 1071'. Insert float set 1026'. Cemented w/200 sx "H" + 12% Thixad + 10#/sx Gilsonite + 2% CaCl2 (yield 1.55, wt 14.6). + 800 sx PSL "C" + 10#/sx Gilsonite + 3% CaCl2 (yield 1.94, wt 12.4). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 3:45 AM 8-15-92. Bumped plug to 1000 psi, float held OK. Circulated 210 sacks. WOC. Drilled out 11:45 PM 8-15-92. WOC 20 hours. NU and tested. Reduced hole to 8-3/4" and resumed drilling. 10 14. I hereby certify that the foregoing is true and correct Date 8-20-92 Title Production Supervisor (This space for Federal or State office use) Date Title Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.