State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

Submit 3 Copie
to Appropriate
to Appropriate District Office

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088 WELL API NO. 30-015-27098

P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease							
DISTRICT III	1992 STATE X FEE							
1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No. E-10167							
SUNDRY NOTICES AND REPORTS ON WELL								
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN I	OR PLUG BACK TO A 7 Lease Name or Unit Agreement Name							
DIFFERENT RESERVOIR. USE "APPLICATION FOR PEF (FORM C-101) FOR SUCH PROPOSALS.)	MIT.							
1. Type of Well:								
OIL OAS OTHER	Boyd "X" State Com							
2. Name of Operator	8. Well No.							
YATES PETROLEUM CORPORATION	2							
3. Address of Operator	9. Pool name or Wildcat							
105 South 4th St., Artesia, NM 88210	North Dagger Draw U/Penn							
4. Well Location								
Unit Letter L: 1980 Feet From The South	Line and 860 Feet From The West Line							
·								
Section 29 Township 19S Ran								
10. Elevation (Show whether DF, RKB, RT, GR, etc.)								
3532'	GR ////////////////////////////////////							
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data								
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:							
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING							
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT							
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB X							
OTHER:	OTHER:							
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed								

work) SEE RULE 1103.

Spudded 26" hole with Auger Air 10:15 AM 11-21-92. Set 40' of 20" conductor pipe. Notified NMOCD, Artesia, of spud time. Resumed drilling 14-3/4" hole 10:15 AM 11-30-92. Ran 25 joints 9-5/8" 36# J-55 casing set 1100'. Guide shoe set 1100', insert float set 1056'. Cemented w/700 sx H/L with 1/2#/sx Flocele + 10#/sx Gilsonite + 3% CaCl2 (yield 1.99, wt 12.7). Tailed in w/200 sx Class "C" Neat with 2% CaCl2 (yield 1.32, wt 14.8). PD 1:30 PM 11-29-92. Bumped plug to 450 psi, float held OK. Circulated 59 sacks to pit. WOC. Drilled out 10:15 AM 11-30-92. WOC 20 hours and 45 mins. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the infor					
SIGNATURE LL	LATURE Le anita Doublett		The Production	n Supervisor	DATE 12-1-92
TYPE OR PRINT NAME	Juanita Goodlett		•		тецерноне но. 505/748-147
(This space for State Use)	ORIGINAL SIGNED BY			÷:	DEC 1 2 1992
. ***	MIKE MILLIAMS	7777 F			DATE:

CONDITIONS OF APPROVAL, IF ANY: