

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Enert Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-27099

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-10167

7. Lease Name or Unit Agreement Name

Boyd X State

8. Well No.

3

9. Pool name or Wildcat

N. Dagger Draw Upper Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter J : 1980 Feet From The South Line and 1980 Feet From The East Line

Section 29

Township 19S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3510' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER: ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, resume drilling, surface casing and cement ☒

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with Frank's Rat Hole at 2:00 PM 3-31-94. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD of spud time. Resumed drilling a 14-3/4" hole with rotary tools at 6:00 AM 4-2-94.

TD 1124'. Ran 25 joints of 9-5/8" 36# J-55 (1125.78') of casing set at 1124'. 1-Texas Pattern notched guide shoe set at 1124'. Insert float set at 1078.90'. Cemented with 100 sacks Class "H", 12% Thixad, 10#/sack gilsonite, 1/2#/sack celloseal and 2% CaCl2 (yield 1.56, weight 14.6) and 900 sacks Pacesetter Lite "C", 10#/sack gilsonite, 1/2#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.4). Tailed in with 200 sacks Class "C" Neat and 2% CaCl2 (yield 1.34, weight 14.8). PD 4:30 AM 4-4-94. Bumped plug to 800 psi, OK. Circulated 180 sacks to pit. WOC. Drilled out at 10:45 PM 4-4-94. WOC 18 hours and 15 minutes. Nippled up and tested to 1000# for 15 minutes. Cut off and welded on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Clerk

DATE April 5, 1994

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

APPROVED BY

TITLE

DATE

APR 8 1994