FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator yates Petr Corp.			Laasc	Lease fills "KW" Irish Hills "JE" St, Com			Well #3		
Location of Well	Unit A	Section 2			1	Range 24	County Cddy		
Drilling Contractor	Type of Equipment								
APPROVED CASING PROGRAM X Witness									
Size of Hole Size		of Casing	-	Weight Per Foot		or Used	Depth	Sacks	Cement
171/2 + 133/8		3/8	48#			7	400	400	Circ
1214	21/4 × 85/8		24#		•		950	570	Circ
77/8	17/8 51/2		15.5 +17#				9200	400	
Casing Data:									
Surfacejoints ofinch# Grade									
(Approved) (Rejected)									
Inspected bydate									
Cementing Program									
Size of hole 143/4" Size of Casing 95/8" Sacks coment required									
Type of Shoe usedFloat collar usedBtm 3 jts welded									
TD of hole 1070' Set 1070' Feet of 95%" Inch 36 # Grade 5.55									
New-used csg. @ with 200 2% cc sacks neat coment around shoe									
+ 850 sax Hull. Lite additives $\frac{1}{2} \frac{\pi}{2} \frac{f \log_{0}}{10} \frac{10 \frac{\pi}{2} g \log_{0} \frac{1}{2} g$									
Cement circulated Ves No. of Sacks 125sr									
Cemented by Halliburton Witnessed by Mike Stublefield									
Temp. Survey ran @ (AM) (PM) Date top cement @									
Casing test @(AN) (PM) Date									
Nethod Used Witnessed by									
Checked for shut off @ (AM) (PM) Date									
Method used Witnessed by									
Remarks:									
Last dilg breaks 882									