

+  
clsr  
up

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED

MAR 04 1993

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line

Section 2 Township 19S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3703' GR

WELL API NO.

30-015-27172

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

L-2764

7. Lease Name or Unit Agreement Name

Irish Hills KW State

8. Well No.

3

9. Pool name or Wildcat

Undesignated

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: Retest Canyon; plugback & test Yeso <input checked="" type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to straddle and test top two Canyon zones perforated 7491-94' (4 holes) and 7522-25' (4 holes). Will re-stimulate Canyon or abandon Canyon. If appropriate, test Yeso as follows:

- 1) POOH w/RBP and packer.
- 2) Set CIBP at 8420' w/35' cement on top.
- 3) Set CIBP at 7960' w/35' cement on top.
- 4) Straddle Canyon zones 7522-25' and 7491-94'. Set RBP  $\pm$  7590' and packer  $\pm$  7450. Swab test and evaluate.
- 5) If decision is made to abandon Canyon, POOH w/tools and set CIBP  $\pm$  7450' w/35' cement.
- 6) Run GR/CCL/CGL from 5200-2000'. Evaluate bond across Yeso.
- 7) Perforate Yeso 2578-87', 2617-24', 2713-38' (total 24 holes).
- 8) Acidize zones in two stages with 2000 gals 15% NEFE + balls.
- 9) Will frac if necessary with 60000 gals 30# linear gel with 63000# 20/40 sand and 45000# 12/20 sand.
- 10) Put well on pump.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-4-93  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Mark Bell TITLE Geologist DATE 3-5-93  
CONDITIONS OF APPROVAL, IF ANY: