			DEALOR DODS. COMPLESSION
		in a care in an a	Extesia, NA 88210 C
(June 1990) (June 1990) (JUN) BUREAU OF I BUREAU OF I SUNDRY NOTICES Do not use this form for proposals to dri	TED STATES T OF THE INTERIOR LAND MANAGEMENT AND REPORTS ON W III or to deepen or reentr	y to a different reservoir.	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM 42787 6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation
1. Type of Well			475
KX Well Gas Other			8. Well Name and No.
2. Name of Operator			Ocotillo ACI Federal #2
YATES PETROLEUM CORPORATION	(505)	748-1471)	9. API Well No.
3. Address and Telephone No.			30-015-27184
105 South 4th St., Artesia, NM 88210			10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Du		- · ·	South Dagger Draw U/Penn
Unit P, 660' FSL & 660' FEL, 5	Section 10-T20S-R24	4E	11. County or Parish, State
			Eddy, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATU	JRE OF NOTICE, REPOR	
TYPE OF SUBMISSION	TYPE OF ACTION		
·			
Notice of Intent			Change of Plans
XX Subsequent Report	Plugging E		New Construction Non-Routine Fracturing
Final Abandonment Notice	Casing Re		X Water Shut-Off
	Altering C	Casing	Conversion to Injection
	X Other Sp	oud, Set Surface Csg	
	· · · · · · · · · · · · · · · · · · ·		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 26" hole 3:00 PM 10-30-93. Set 40' of 20" conductor pipe and cement to surface. Notified BLM, Carlsbad, NM, of spud. Resumed drilling 14-3/4" hole 5:30 AM 10-6-93. Drilling with no returns. Mixed LCM with no returns. Ran 25 joints 9-5/8" 36# J-55 ST&C casing set 1120'. Guide shoe set 1120', insert float set 1077'. Cemented w/400 sx PSL "C" with 10#/sx Gilsonite, 1/2#/sx Celloseal, 3% CaCl2 (yield 2.02, wt 12.4). Tailed in w/200 sx Class "C" Neat with 2% CaCl2 (yield 1.34, wt 14.8). PD 5:00 PM 11-4-93. Bumped plug and float held. Cement did not circulate. WOC 4 hours. Ran Temp. Survey and found TOC at 775'. Ran 9 stages of 1". Cemented w/1200 sx PSL "C" and Class "H" w/additives. Tag stage 9 at 145'. PD stage 9 at 1:50 PM 11-6-93. WOC. Drilled out at 5:30 AM 11-6-93. WOC 36 hours and 30 minutes. NU and tested to 1000 psi for 15 minutes. Cut off and weld on flow nipple. Reduced hole to 8-3/4" and resumed drilling. 			
14. I hereby certify that the foregoing is true and correct	······································		
signanuta Doudle	Tide Producti	on Supervisor	
(This space for Federal or State office use)			
Approved by Conditions of approval, if any:	Title	·	Date
Conditions of approval, if any:			9 1993
			SJS

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. _____

the last the Development