restaurant

Form 3160-5 (J

## UNITED STATES

FORM APPROVED

June 1990)	DEPARTME	NT OF THE INTERIOR	1 1 1993	Budget Bureau No. 1004-0135 Expires: March 31, 1993	
	BUREAU OF I	LAND MANAGEMENT	O. C. D.	5. Lease Designation and Serial No. NM 045276	
Do not us	e this form for proposals to dr	AND REPORTS ON WELL ill or to deepen or reentry to R PERMIT—" for such propose	a different reservoir.	6. If Indian, Allottee or Tribe Name	
	SUBMIT	IN TRIPLICATE		7. If Unit or CA, Agreement Designation	
1. Type of Weil	I			-	
XX Oil Gas Well Other  2. Name of Operator				8. Well Name and No. PRESTON FEDERAL #6	
Conoco Inc.				9. API Well No.	
3. Address and Telephone No. 10 Desta Drive STE 100W. Midland, TX 79705 (915)686-5424				30-015-27187  10. Field and Pool, or Exploratory Area -SO. DAGGER DRAW/CEMENTARY	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				MORROW  11. County or Parish, State	
990' FNL & 460' FEL, SEC. 35, T-20S, R-24E, UNIT LTR 'A'				EDDY, NM	
12. C	CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE	OF NOTICE, REPOR	<u></u>	
	TYPE OF SUBMISSION				
	Notice of Intent	Abandonment		Change of Plans	
_		Recompletion		New Construction	
1	Subsequent Report	Plugging Back		☐ Non-Routine Fracturing ☐ Water Shut-Off	
[	Final Abandonment Notice	Casing Repair  Altering Casing		Conversion to Injection	
		XX Other SET PI	RODUCTION CSG	Dispose Water (Note: Report results of multiple completion on Well	
12 Deceribe Pro	proced or Completed Operations (Clearly state a	Il nertinent details, and give pertinent dates, i	ncluding estimated date of startin	Completion or Recompletion Report and Log (orm) g any proposed work. If well is directionally drilled,	
give sul	bsurface locations and measured and true verti	cal depths for all markers and zones pertine	nt to this work.)*		
DRILLED 8 3/4" HOLE TO TD OF 9650° ON 1-15-93. 1-16-93 RIH W/ 217 JTS 7" 26# L-80 & K-55 LT&C CSG SET @ 9743°. SHOE SET @ 9473° AND COLLAR SET @ 9430°. 1ST STAGE CMT. LEAD SLURRY 300 SX PREMIUM PLUS + 5PPS SALT + 5PPS GILSONITE + 1/4 PPS FLOCELE. TAIL SLURRY 550SX PREMIUM PLUS + 8PPS SILICA + .8% HOLAD 322 + 5# GILSONITE +					
					FLOCKLE. TAIL SLURRY 550SX PREMIUM PLUS + 8PPS SILICA + .8% HOLAD 322 + 5# GILSONITE + 2.4 PPS SALT + .25% CFA3. SECOND STAGE LEAD SLURRY 800 SX PREMIUM PLUS + 5 PPS SALD + 1/4 PPS FLOCELE.
TAIL SLURRY 100 SX PREMIUM PLUS, CEMENT RETURNS 160 SX. RELEASED RIG AT NOON ON 1-17-93.					
RELEASED RIG AT NOON ON 1-17-93.					
REPLICATION OF THE PROPERTY OF					
TAIL SLURRY 100 SX PREMIUM PLUS, CEMENT RETURNS 160 SX. RELEASED RIG AT NOON ON 1-17-93.					
			S. O.C.	6 <sup>7393</sup>	
			Sa	* N.M.	
			Car OIST	W Mexico	
14. I hereby ce	rtify that the foregoing is true and correct				
Signed	Bet & Buil	Title SR. REC	GULATORY SPEC	Date	
(This space	fer Federalor, State office (Se)	ng record	THE ENGINEER	1 18-03	
Approved t Conditions		Title		Date	
Title 18 11 5 C	Section 1001 makes it a grime for any nerso	n knowingly and willfully to make to any de	partment or agency of the Unite	d States any false, fictitious or fraudulent statements	
or representatio	as lest id any matter within its jurisdiction.				