

15F
DP

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27189
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Patriot AIZ Com
8. Well No. 2
9. Pool name or Wildcat North Dagger Draw U/Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3523' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter 0 : 760 Feet From The South Line and 1980 Feet From The East Line Section 20 Township 19S Range 25E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3523' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production Casing, Perforate, Treat <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8250'. Reached TD 1-13-93. Ran 201 joints 7" 23# and 26# J-55 and N-80 casing set 8250'. Float shoe set 8250', float collar set 8211'. DV tool set 5605'. Cmt'd in two stages. Stage I - 600 sx PP "C" w/8# Silicalite, 6/10% Halide 322 w/3% Salt (yield 1.80, wt 13.6). PD 9:00 PM 1-14-93. Bumped plug to 1500 psi for 2 mins. Circulated 109 sacks. Circulated thru DV tool 3-1/2 hours. Stage II - 800 xx PP Lite "C" w/5#/Salt, 5# Gilsonite, 1/4# Flocele (yield 1.89, wt 12.4), followed by 100 sx Class "C" Neat (yield 1.32, wt 14.8). PD 2:45 AM 1-15-93. Bumped plug to 2800 psi for 2 mins. Circulated 195 sacks cement. Float and casing held OK. WOC 24 hrs. Drilled DV tool at 5605'. Perforated Canyon 7645, 7647 and 7648' (2 SPF-6 holes). Acidized perms 7645-7648' w/600g. 15% Haliiburton MCA.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 1-31-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

APPROVED BY MIKE WILLIAMS TITLE SUPERVISOR DISTRICT II DATE JAN 29 1993

CONDITIONS OF APPROVAL, IF ANY: