

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-27190

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
E-2943

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Anadarko Petroleum Corporation

3. Address of Operator
PO Drawer 130, Artesia, NM 88211

4. Well Location
Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line

Section 10 Township 19S Range 29E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3364' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Set 40' of 14" conductor pipe in 20" hole and ready-mixed to surface.
2. MIRU Capstar Rig #1. Spudded 12 1/4" hole at 2100 hrs 11-21-92. Lost circulation at 53' Dry drilled to 305' with fresh water native mud.
3. Ran 24# 8 5/8" casing and set at 299'. Cemented with 200sx Class C cement with 2% CaCl. Had no circulation while cementing. Ready-mixed to surface with 8 1/2 yards cement. WOC-18 hrs.
4. Installed BOP and tested to 500#. OK. Drilled to 2400' with salt gel mud. Ran logs. WIH 15.5# 5 1/2" casing to 2399' and cemented with 265sx Premium Plus 50/50 Poz A cement and tailed in with 210 sx Haliburton Light cement. Circulated 10 sx to pit. Plug down at 800 hrs 11-27-92.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Braswell TITLE Field Foreman DATE 11-30-92
TYPE OR PRINT NAME Mike Braswell TELEPHONE NO. 677-2411

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE DEC 7 1992

CONDITIONS OF APPROVAL, IF ANY: