

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

JUL 19 1993

WELL API NO.

30-015-27314

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG-864

7. Lease Name or Unit Agreement Name

Amole AMM State Com

8. Well No.

1

9. Pool name or Wildcat

North Dagger Draw Upper Penn

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter M : 760 Feet From The South Line and 660 Feet From The West Line

Section 16

Township 19S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3500' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforations and acid treatment ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cleaned location and set anchors. Dressed off 7" casing. Moved in and rigged up pulling unit. TIH w/bit, stabilizer, drill collars and tubing. Drilled out DV tool at 5600'. Tested to 1500 psi. TIH and tagged PBTD at 8310'. Displaced hole with 2% KCL. TOOH. Laid down drill collars. TIH w/bit and scraper to 5700'. TOOH. WIH and perforated 7772-7804' w/24 .42" holes and 7692-7734' w/28 .42" holes. TIH w/RBP and packer. Straddled perforations 7772-7804'. Acidized with 8000 gallons 20% NEFE gelled acid with scale and paraffin inhibitor. Moved tools and straddled perforations 7692-7734'. Acidized with 12000 gallons 20% NEFE gelled acid with scale and paraffin inhibitor. Swabbing.

Released tools and turned to production to run sub-pump.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE Production Clerk

DATE July 7, 1993

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR DISTRICT I

APPROVED BY

TITLE

DATE

JUL 26 1993

CONDITIONS OF APPROVAL, IF ANY: