

YATES PETROLEUM CO. DRATION

Conoco AGK Federal Com #14

Section 15 T20S-R24E, 660' S & 660' W

Comments

4/93 & 5/93

WIH whit and drill collars on 2 7/8" I-55 tubing. Prep to pull POH and make string mill run. Had 15' of cement on top of DV tool. Made scraper run to TD. POH. Laid down drill collars. Rigged up wireline. Ran CBL and collar log from TD to 5000'. Perfed Canyon Dolomite w/4" casing gun (.50" holes), and 180 deg phasing w/1000# on casing: 7609', 7610', 7612', 7614', 7616' (2 SPF - 10 holes); 7592', 94', 96', 98' (2 SPF - 8 holes); 7540', 42', 44', 46', 48', 50' (2 SPF - 12 holes); 7525', 26', 28', 32', 34' (2 SPF - 10 holes); 7510', 13', 15' (2 SPF - 6 holes). WIH w/RBP and packer. Tested RBP to 2500#. Straddled perfs 7592-7616. Treated w/12000 gals 20% HCL and scale inhibitor and 36 balls. Straddled perfs 7510-7550'. Treated w/18000 gals of 20% NBF and scale inhibitor and 33 ball sealers. Swabbed from 4000' to surface. Shut well in.

CASING

7" 26# N-80	282.95'
7" 26# J-55	468.82'
7" 26# J-55	2184.61'
7" 23# J-55	3754.23'
7" 26# J-55	1232.52'

