

clst
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27335
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Hooper AMP
8. Well No. 1
9. Pool name or Wildcat North Dagger Draw Upper Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter M : 820 Feet From The South Line and 660 Feet From The West Line

Section 21 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3503' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 8:30 AM 4-6-93. Set 40' of 20" conductor pipe. Notified NMOCD, Artesia, NM of spud time. Resumed drilling 14-3/4" hole 10:15 AM 4-8-93. TD 14-3/4" hole 9:30 PM 4-9-93. Ran 26 joints 9-5/8" 36# J-55 casing set 1165'. Guide shoe set 1165'. Insert float set 1120'. Cemented w/900 sx PSL "C" 65/35/6 with 10#/sx Gilsonite, 1/2#/sx Celloseal + 3% CaCl2 (yield 1.94, wt 12.4). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 5:00 AM 4-10-93. Bumped plug to 600 psi, float held OK. Circulated 190 sx to pit. WOC. Drilled out 11:00 PM 4-10-93. WOC 18 hrs. NU and tested to 1000 psi for 15 minutes, OK. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-13-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE APR 26 1993

CONDITIONS OF APPROVAL, IF ANY: