

151
P

DISTRICT I
P.O. Box 1930, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
600 Rio Puerco Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

MAY 25 1992

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN TO PLACE BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐		WELL API NO. 30-015-27335
2. Name of Operator YATES PETROLEUM CORPORATION		5. Indicate Type of Lease STATE ☐ FEE ☒
3. Address of Operator 105 South 4th St., Artesia, NM 88210		6. State Oil & Gas Lease No.
4. Well Location Unit Letter M : 820 Feet From The South Line and 660 Feet From The West Line Section 21 Township 19S Range 25E NMPM Eddy County		7. Lease Name or Unit Agreement Name Hooper AMP
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3503' GR		8. Well No. 1
		9. Pool name or Wildcat North Dagger Draw Upper Penn

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: Perforations & acid ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Made cut off on 7" casing. WIH w/drill bit and collars on tubing. Drilled DV tool at 5606'. Cleaned out hole to float collar at 8244'. Displaced hole with 2% KCL. POOH. Laid down drill collars and string mill. Ran Bond log. RIH and perforated 7813-7817' w/6 .50" holes as follows: 7813, 15, & 17'. WIH w/packer and set above perforations. Acidized perforations 7813-7817' w/500 gallons 15% NEFE (HCL) with scale inhibitor and paraffin inhibitor. Evaluating.

TIH w/RBP, packer and tubing. Straddled perforations 7813-7817'. Acidized with 2000 gallons 20% NEFE acid. Pulled up and set RBP at 7797'. Spot 5000 gallons 15% NEFE acid. TOOH w/tubing and packer. TIH and perforated 7775-7781' w/8 .50" holes as follows: 7775, 77, 79 & 7781' (2 SPF). TIH w/packer and tubing. Set packer at 7752'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE May 24, 1993
TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

MAY 28 1993

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: