

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Enr Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27355
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-10167
7. Lease Name or Unit Agreement Name Boyd X State
8. Well No. 4
9. Pool name or Wildcat North Dagger Draw U/Penn

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471
4. Well Location Unit Letter <u>K</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>1980</u> Feet From The <u>West</u> Line Section <u>29</u> Township <u>19S</u> Range <u>25E</u> NMPM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3521' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 2:00 PM 10-10-93 with Frank's Rathole Service. Set 40' of 20" conductor. Redi-mix to surface. Resumed drilling 14-3/4" hole 3:30 PM 10-14-93. Ran 26 joints 9-5/8" 36# J-55 casing set 1165'. Guide shoe set 1165', insert float set 1121'. Cemented with 200 sx "H" + 12% Thixad, 10#/sx Gilsonite + 1/2#/sx Celloseal + 2% CaCl2 (yield 1.56, wt 14.6). and 800 sx PSL "C" + 5#/sx Gilsonite + 1/4#/sx Celloseal + 3% CaCl2 (yield 1.98, wt 12.4). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 11:38 PM 10-15-93. Bumped plug to 1200 psi, float held OK. Circulated 195 sacks to pit. WOC. Drilled out 6:45 PM 10-16-93. WOC 19 hours and 5 mins. NU and tested to 1000 psi for 15 minutes, OK. Cut off and weld on flow nipple. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-19-93  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

NOV 12 1993