

c15f  
OpDISTRICT I  
P.O. Box 1980, Hobbs, NM 88240DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27356
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Hooper AMP
8. Well No. 2
9. Pool name or Wildcat N. Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3498' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line Section 21 Township 19S Range 25E NMPM Eddy County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Spud, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with Frank's Rat Hole Service at 3:30 PM 6-2-93. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD of spud.

Resumed drilling with rotary tools (14-3/4" hole) at 8:00 AM 6-4-93.

TD 1207'. Ran 28 joints of 9-5/8" 36# J-55 (1212.08') of casing set at 1207'. 1-Texas Pattern notched guide shoe set at 1207'. Insert float set at 1172'. Cemented with 900 sacks PSL "C", 3% CaCl<sub>2</sub>, 10#/sack gilsonite and 1/2#/sack celloseal (yield 1.94, weight 12.4). Tailed in with 200 sacks Class "C" Neat 2% CaCl<sub>2</sub> (yield 1.32, weight 14.8). PD 8:58 AM 6-6-93. Bumped plug to 700 psi, float held OK. Cement did not circulate. WOC Drilled out at 5:15 AM 6-7-93. WOC 20 hours. Nippled up and tested to 1000 psi for 15 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 1, 1993  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JUL 20 1993  
CONDITIONS OF APPROVAL, IF ANY: