Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89 cist

DISTRICT I	OIL CONSERVATION		WELL API NO.
P.O. Box 1980, Hobbs NM 88240	P.O. Box 208		30-015-27465
P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	8/304-2088	5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease No. E-10083
	TICES AND REPORTS ON WELL		
DIFFERENT RESE	OPOSALS TO DRILL OR TO DEEPEN O ERVOIR. USE "APPLICATION FOR PERA D-101) FOR SUCH PROPOSALS.)	R PLUG BACK TO A //IT"	7. Lease Name or Unit Agreement Name INDIAN HILLS STATE COMM
1. Type of Well: OIL GAS WELL WELL	OTHER SWD	1	
2. Name of Operator			8. Well No.
Marathon 0il Company			9. Pool name or Wildcat
3. Address of Operator P.O. Box 552, Midland,	TX 79702		
4. Well Location Unit Letter F: 16	50 Feet From The NORTH	Line and 19	80 Feet From The WEST Line
Section 36	Township 20-SOUTH Ra	nge 24-EAST	NMPM EDDY County
	10. Elevation (Show whether	r DF, RKB, RT, GR, etc 3625 G.L.	-3
11. Check A	ppropriate Box to Indicate		Report, or Other Data
	INTENTION TO:	SUE	SEQUENT REPORT OF:
	PLUG AND ABANDON	REMEDIAL WORK	☐ ALTERING CASING ☐
PERFORM REMEDIAL WORK LITEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS. D PLUG AND ABANDONMENT
PULL OR ALTER CASING		CASING TEST AND CE	MENT JOB
	П	OTHER:	
OTHER:	(Clearly state all partinent date		ies, including estimated date of starting any standed
DRILLED CIBP 7681'-768 0 2.5 BPM 0 600 PSI. F PSI. EST. INJ. RATE TH 100 SL CLASS 'H'. SQUE BBLS CEMENT. POOH. WOI 7870'. CIRC HOLE & PRI 4000'. RELEASED PKR, I PULLED PKR. RIH W/ 6 CEMENT PLUG 9170' - 82 P.U. 6 1/2" BIT, TAGGI SET 8000'& LOAD BACKS: 100 PSI. RIG DOWN PULI 4/12/95 MIRU ROTARY TO CHOKE & KILL LINES & I	HRU RETAINER © 3.5 BPM, 2 EEZED INTO PERFS 7582'-7' LC 36 HRS. RIH & TAGGED (ESSURE UP ON CSG. TO 110 LOADED HOLE, SET PKR © 7' 1/2" BIT, TAGGED CIBP © 2', MILLED ON MODEL 'D' ED FLOAT COLLAR © 9615', IDE & TESTED TO 1000 PSI LING UNIT. DOLS. N.U. 11" 3M DUAL R MANIFOLD, SURFACE LINES	SET # 7501'. TES 250 PSI. MIXED 630' # 2600 PSI CEMENT # 7490' 0 PSI. RAN RTTS 351', TESTED CA 9071', DRILLED PACKER # 9182, DRILLED COLLAR ., PULLED TBG T AM BOP'S AND AN TO 300/3000 PSI	TED TBG TO 3000 PSI, CSG TO 500 250 5X COMSS 'AT THE AMERICAL AT CF 14 & . STUNG OUT OF RETAINER RO 49 DRILLED CEMENTON STATEMENT TO TO 7540' SWABBED TUBING TO SING TO 2300 PSI. HELD OK. CIBP 9071'- 9074'. DRILLED
I hereby certify that the information above	e is true and complete to the best of my knowled	ge and belief.	
SIGNATURE Word - Quice	an FOR DPN	mu <u>DR</u> LG, 301	
TYPE OR PRINT NAMEWALT J. D	UEEASE		TELEPHONE NO.915-682-1626
(This space for State Use) ORIGINA APPROVED BY	L SIGNED BY TIM W. GUM THSUPERVISOR	т.	MAY 1 0 1995
CONDITIONS OF APPROVAL, IF ANY	I II WAT PROTECTION		