

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
SEP 24 1993

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive STE 100W, Midland, TX 79705 (915)686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 1980' FEL, SEC. 35, T-20S, R-24E, UNIT LTR 'B'

5. Lease Designation and Serial No.

NM 045276

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

PRESTON 35N FEDERAL #9

9. API Well No.

30-015-27626

10. Field and Pool, or Exploratory Area

SO. DAGGER DRAW PENN

11. County or Parish, State

EDDY, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other SET PRODUCTION CSG.

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-19-93 DRILLED TO TD AT 8100'. GIH W/ 180 JTS 7" 26# K-55 LT&C CSG SET @ 8100'. SHOE SET @ 8100' AND COLLAR @ 8054'. FIRST STAGE LEAD SLURRY 280 SX PREMIUM PLUS H/L W/ 5 pps GILSONITE + 1/4 pps FLOCELE. TAIL SLURRY 250 SX PREMIUM PLUS W/ 8 pps SILICALITE + 0.7% FLOBLOCK + 0.4% ECANOLITE. BUMP PLUG @ 6:45 pm ON 9-20-93 W/ 1800 PSI. SECOND STAGE LEAD SLURRY 605 SX PREMIUM PLUS H/L W/ 1/4 pps FLOCELE + 5 pps GILSONITE. TAIL SLURRY 100 SX PREMIUM PLUS NEAT. BUMPED PLUG @ 12:30 am ON 9-21-93. RELEASED RIG ON 9-21-93. WAITING ON COMPLETION RIG.

BLM NOTIFIED @ 12 NOON ON 9-20-93.

14. I hereby certify that the foregoing is true and correct

Signed

David R. Kennedy

Title

SR. REGULATORY SPEC

Date 9-21-93

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date