

REVISED SUNDRY

NM OIL CONS COMMISSION
Drawer DDForm 3160-S
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

DEC 10 1993

Artesian Form NM 008510
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other DRILLING WELL

2. Name of Operator

SPENCE ENERGY COMPANY

Ph. 214-739-0027

3. Address and Telephone No. 4849 Greenville Ave., Ste. 381
Dallas, Texas 75206

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL, 2305' FWL, Sec. 23-19S-30E

(Unit K)
(NESW)

5. Lease Designation and Serial No.

NM-4350

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

NA

8. Well Name and No.

Unocal Federal 23 No. 1

9. API Well No.

10. Field and Pool, or Exploratory Area

North Hackberry -
Yates Seven Rivers

11. County or Parish, State

Eddy County, N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒
- Notice of Intent
-
- ☐
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☐
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☒
- Altering Casing
-
- ☐
- Other
-
- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☒
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Sundry Report dated 11-03-93 is revised as follows to correct typographical error in perforated interval:

Drill out cement from 1730' to T.D. of 1962'; fill hole from 1800' to 1962' with sand to protect lower perforations. Run 4" flush joint 11.4# liner from surface to 1800'.

Cement back to surface; drill out shoe and circulate sand and put perforated interval 1810'-24' and 1868'-1880' on production.

14. I hereby certify that the foregoing is true and correct

Signed Terry W. Long
(This space for Federal or State office use)

Title Permit Agent

Date 11/29/93

Approved by (ORIG. SGD.) DAVID R. GLASS
Conditions of approval, if any:

Title Petroleum Engineer

Date DEC 10 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side