

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

nm oil  
Drawer B  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

OCT 19 1993

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 660' FEL (NENE, Unit A) Section 31-T19S-R24E

5. Lease Designation and Serial No.

NM-76936

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sunflower AHW Fed #2

9. API Well No.

30-015-27525

10. Field and Pool, or Exploratory Area

Undes. Morrow

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud, resume drilling,  
surface casing & cement

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 26" hole at 4:00 PM 8-31-93. Set 40' of 20" conductor pipe. Cemented to surface.  
NOTE: Notified Shannon Shaw w/BLM of spud. Resumed drilling a 17-1/2" hole with rotary tools at 12:30 PM 9-13-93. Drilled to 383'. Ran 8 joints of 13-3/8" 54.5# J-55 (376.08') of casing set at 376'. 1-Texas Pattern notched guide shoe set at 376'. Insert float set at 328.94'. Cemented with 100 sacks "H", 12% Thixset, 1/2# flocele, 10# gilsonite and 2% CaCl2 (yield 1.53, weight 14.6). Tailed in with 200 sacks "C", 1/2# flocele, 10# gilsonite and 2% CaCl2 (yield 14.8, weight 1.32) and 200 sacks "C" 2% CaCl2 (yield 14.8, weight 1.32). PD 9:00 AM 9-14-93. Bumped plug to 150 psi, OK. Circulated 25 sacks. WOC. Drilled out at 3:00 AM 9-15-93. WOC 18 hours. Nippled up and tested to 500# for 15 minutes. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

ACCEPTED FOR RECORD  
J. Lara  
OCT 18 1993  
CARLSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date Sept. 23, 1993

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side