

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

OCT - 7 1993

WELL API NO. 30-015-27641
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Voight AJD Com
8. Well No. 3
9. Pool name or Wildcat North Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3525' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator YATES PETROLEUM CORPORATION ✓
3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471
4. Well Location Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line Section 29 Township 19S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
Spudded 26" hole 10:00 AM 9-10-93. Set 40' of 20" conductor pipe. Redi-mix to surface. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 6:30 PM 9-20-93. Ran 25 joints 9-5/8" 36# J-55 ST&C casing set 1116'. Guide shoe set 1116', insert float set 1076'. Cemented w/900 sx PSL w/5#/sx Gilsonite + 1/4#/sx Celloseal + 3% CaCl2 (yield 1.99, wt 12.4). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.33, wt 14.8). PD 9:00 PM 9-22-93. Bumped plug to 800 psi, float held OK. Cement did not circulate. WOC 4 hrs. Ran temperature survey and found TOC at 150'. Ran 1". Cemented with 300 sx Class with 2% CaCl2. WOC and tested casing to 1000 psi. Drilled out 6:45 PM 9-23-93. WOC 21 hours 45 minutes. Reduced hole to 8-3/4" and resumed drilling. Cementing operations witnessed by Mike Stubblefield, NMOCD, Artesia, NM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-5-93  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

OCT 19 1993

APPROVED BY SUPERVISOR, DISTRICT II TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY: