

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-27641

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location
Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line
Section 29 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3525' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Production Casing, Perforate, Trt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8270'. Reached TD 10-9-93. Ran 202 joints 7" 23# and 26# J-55 and N-80 casing set 8270'. Float shoe set 8267', float collar set 8226'. DV tool set 5618'. Cemented in two stages as follows; Stage I - 625 sx Class "H" w/5#/sx CSE, 5#/sx Gilsonite, 1/4#/sx Celloseal, .65% CF-14 (yield 1.31, wt 15.1). PD 5:45 AM 10-11-93. Bumped plug to 1250 psi for 1 min, OK. Circulated 171 sacks. Circulated thru DV tool 2-3/4 hours. Stage - 875 sx PSL "C" (65/35/6), 5#/sx Gilsonite, 5#/sx Salt, 1/4#/sx Celloseal, .4% CF-14 (yield 1.98, wt 12.4). Tailed in 100 sx Class "H" Neat (yield 1.17, wt 15.6). PD 10:18 AM 10-11-93. Bumped plug to 1500 psi for 1 minutes, float and casing held OK. Circulated 37 sacks. WOC 24 hours. Drill DV tool at 5618'. Tested to 2000 psi. Displace hole with 2% KCL. Perforated 7810, 12, 14' w/6 - .50" holes (2 SPF). Acidized perforations 7810-14' w/1000 gals 20% NEFE acid. 10-16-93. Turned to production to run sub pump.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-21-93

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR DISTRICT I

APPROVED BY

TITLE

DATE

NOV 22 1993

CONDITIONS OF APPROVAL, IF ANY: