form 3 ist	UNI	STATES STATES		
June 1990)	DEPARTMEN	JF THE INTERIOR		
	BUREAU OF I	AND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993	
	SUNDRY NOTICES	AND REPORTS ON WELLS	5. Lease Designation and Serial No.	
o not use this for	rvoir. NM10190			
	Jse "APPLICATION FO	R PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name	
	N/A			
Type of Well			7. If Unit or CA, Agreement Designation	
	14-08-001-11572			
Name of Operator		8. Well Name and No.		
	RGY CORPORATION (NEVAI	DA)		
Address and Telephone	No.	East Shugart Unit #42 9. API Well No.		
20 NORTH B	ROADWAY, SUITE 1500, OKI			
Location of Well (Foot	age. Sec., T., R., M., or Survey De	10. Field and Pool, or Exploratory Area		
330' FNL & 1140'	FEL Sec. A-34-18S-31E	Shugart (Y-SR-Q-G)		
			11. County or Parish, State	
	·····		Eddy, NM	
CHECK A	PPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE	E, REPORT, OR OTHER DATA	
TYPE OF SU		TYPE OF ACTION		
Notice of Intent		Abandonment	Change of Plans	
		Recompletion	New Construction	
Subsequent Report		Plugging Back	Non-Routine Fracturing	
		Casing Repair	Water Shut-Off	
Final Abandonment N	otice	Altering Casing	Conversion to Injection	
		Other	Dispose Water	
			(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled, give subsurf	

NMOCD order #WFX 664; Permit #123-2920-94-A

12-27-94: RIH w/ 4 3/4" bit, csg scrapper & 2 7/8" tbg to 3950'. Che to be sear-w/Hosh D Pulled tbg, scraper & bit. Ran Baker Loc Set pkr (nickle plated) w/stainless steel Model L-316 ON-OFF CONNECTOR + 1.81" "F" profile nipple on 2 7/8" tbg. Set pkr @ 3549'. RU Charger & acidized Queen perfered 1661199512' w/5000 gals 15% NeFe acid using 64 ball sealers. Did not ball out. Over flushed w/70 barrels fresh wtr. Max press 2020 psi, avg press 1750 osi @ 5.1 BPM, ISIP 1450 psi, 5 min 1360 psi, 10 min 1320 psi, 15 min 1290 00 Now of the back to pit. Left lowing to pit overnight. DIST. 2

12-28-94: Released on-off tool. Pulled & LD 120 jts 2 7/8" work string. Ran 2 3/8" fiberglass tbg w/on-off tool on otm. Circ hole clean w/pkr fluid (fresh wtr + corrosion inhibitor). Latched onto pkr w/on-off tool. Press annulus to 500 psi for 30 mins. RD unit. NMOCD notified, but did not witness test. Well converted to injection. WO tie-in to njection system.

4. I hereby certify that the foregoing is true and correct igned,	Title	E. L. Buttross, Jr. District Engineer	Date <u>1/11/95</u>	<u>.</u>	
This space for Federal or State office use) pproved by conditions of approval, if any:	_ Title	ACCEPTED FOR RECORD	Date		72,1 734 777 777 777 777
itle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully and willfully matter within its jurisdiction.	y to make to a	CARESBAD, NEW MEXICO	e, fictitious or fraudulent state	ments or rep	



čΚ

RECEIVED

JAN 0 4 1995

PRODUCTION DEPT.