

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

DEC 20 1993

3. Address and Telephone No.

10 Desta Drive STE 100W, Midland, TX 79705 (915) 686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FEL, SEC. 35, T-20S, R-24E, UNIT LTR 'P'

5. Lease Designation and Serial No.

NM 045276

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

PRESTON FEDERAL #10

9. API Well No.

30-015-27715

10. Field and Pool, or Exploratory Area

SO DAGGER DRAW UP PENN

11. County or Parish, State

EDDY, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other SPUD & SET SURFACE CSG

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12-8-93 SPUD 14 3/4" HOLE, DRILL TO A DEPTH OF 1070'. GIH W/ 25 JTS 9 5/8" 36# K-55 LT&C CSG TO A DEPTH OF 1055'. DEPTH OF SHOE @ 1055'. COLLAR SET @ 1011'. LEAD SLURRY 900 SX HLC + 3% CACLW + 5 pps GILSONITE + .5 pps CELLO. TAIL SLURRY 200 SX CLASS 'C' CMT W/ 2% CACL. DISPLACED W/ 80 bbl FW. BUMPED PLUG @ 2:10 pm ON 12-9-93 W/ 600 PSI. READY MIX CMT TO SURFACE. NOTIFIED BLM @ 7am ON 12-9-93.
12-11-93 CONTINUE DRILLING AN 8 3/4" HOLE.

ACCEPTED
(ORIG. SGD.) DAVID R. GLASS
16 1993

14. I hereby certify that the foregoing is true and correct

Signed

David R. Glass

Title

SR. REGULATORY SPEC

Date

12-13-93

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: