

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-015-27731

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

DEC 03 1993

2. Name of Operator  
YATES PETROLEUM CORPORATION

7. Lease Name or Unit Agreement Name

Carl TP Com

3. Address of Operator  
105 South 4th St., Artesia, NM 88210 (505) 748-1471

8. Well No.  
3

9. Pool name or Wildcat  
South Dagger Draw Upper Penn

4. Well Location  
Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line

Section 22 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3681' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Set production casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 7850'. Reached TD 12:00 PM 11-30-93. Ran 191 joints 7" 23# and 26# J-55 and 26# N-80 casing set at 7850'. Float shoe set 7850', float collar set 7810'. DV tools and casing packer set 7466'. Bottom of packer set 7482'. Cemented in two stages as follows: Stage I - 125 sx "H" + 5#/sx CSE + 5#/sx Gilsonite, .65% CF-14 + 1/4#/sx Celloseal (yield 1.31, wt 15.1). PD 10:30 PM 12-1-93. Bumped plug to 750 psi for 2 minutes. Circulated DV tool 2-3/4 hours. Stage II - 1375 sx PSL "C" 65/35/6, 5#/sx Salt, .4% CF-14, 5#/sx Gilsonite, 1/4#/sx Celloseal (yield 2.01, wt 12.4). Tailed in w/235 sx "H", 5#/sx CSE, 5#/sx Gilsonite, .65% CF-14 and 1/4#/sx Celloseal (yield 1.18, wt 15.6). PD 4:52 AM 12-2-93. Bumped plug to 3600 psi for 3 minutes, float and casing held. Circulated 190 sacks. WOC 18 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-3-93

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

DEC 29 1993

APPROVED BY SUPERVISOR, DISTRICT IV TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY: