

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

FEB - 2 1994

WELL API NO.

30-015-27757

5. Indicate Type of Lease

STATE ☐FEE ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

Mobil AOB

8. Well No.

1

9. Pool name or Wildcat

North Dagger Draw Upper Penn

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒GAS  
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East LineSection 1Township 20SRange 24E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3603' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ALTERING CASING ☐COMMENCE DRILLING OPNS. ☒PLUG AND ABANDONMENT ☐CASING TEST AND CEMENT JOB ☒OTHER: Set surface casing ☒


12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 9:00 AM 1-23-94. Set 40' of 20" conductor casing and cemented to surface. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 12:01 PM 1-25-94. Lost circulation at 247'. Mixed LCM and no returns. Drilled with no returns. Ran 24 joints 9-5/8" 36# J-55 casing set at 1075'. Guide shoe set 1075', insert float set 1030'. Cemented with 200 sx "H" + 12% Thixad + 10# Gilsonite + 2% CaCl2 (yield 1.55, wt 14.6) and 900 sx PSL "C" + 10# Gilsonite (yield 1.98, wt 14.8). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 9:29 PM 1-26-94. Bumped plug to 1000 psi, held OK. Circulated 140 sacks cement. WOC.

Nipped up BOP. Test stack. Installed rotating head. TIH. Test casing to 500 psi. Drilled out at 8:30 PM 1-27-94. WOC 23 hours. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

Production Supervisor

DATE 1-28-94

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

FEB 12 1994

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: