

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Ene Minerals and Natural Resources Department

RECEIVED Form C-103
Revised 1-1-89

DEC 10 1993

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27759
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Sara AHA
8. Well No. 9
9. Pool name or Wildcat South Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3657' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471
4. Well Location Unit Letter J : 1980 Feet From The South Line and 1980 Feet From The East Line Section 15 Township 20S Range 24E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3657' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 12:45 PM 11-29-93. Set 40' of 20" conductor and cemented to surface. Resumed drilling 14-3/4" hole 6:00 AM 12-4-93. Ran 25 joints 9-5/8" 36# J-55 casing set at 1112'. Guide shoe set 1112', insert float set 1068'. Cemented with 200 sx "H" + 12% Thixad + 2% CaCl2 (yield 1.55, wt 14.6), and 625 sx PSL "C" + 1/4#/sx Celloseal + 5#/sx Gilsonite + 3% CaCl2 (yield 1.98, wt 12.4). Tailed in with 200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 4:30 AM 12-6 93. Bumped plug to 750 psi, float held OK. Circulated 220 sacks. WOC. Drilled out 11:00 PM 12-6-93. WOC 18 hours and 30 minutes. Nipped up and tested to 1000 psi for 15 minutes. OK. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-8-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE DEC 29 1993

CONDITIONS OF APPROVAL, IF ANY: