Submit 3 Copies to Appropriate District Office

Ener

State of New Mexico Ainerals and Natural Resources Department

Form C	-103
Revised	1-1-

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

30-015-277	77	7
Indicate Type of Lease		

WELL API NO.

DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410

FEE XX STATE 6. State Oil & Gas Lease No.

TOTAL AND REPORTS ON WELLS			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name		
1. Type of Well: OIL OAS WELL X WELL OTHER	Patriot AIZ Com		
2. Name of Operator	8. Well No.		
YATES PETROLEUM CORPORATION	9. Pool name or Wildcat		
3. Address of Operator 105 South 4th St., Artesia, NM 88210	North Dagger Draw Upper Penn		
4. Well Location South Line and 1980 Feet From The West Line			
Unit Letter N : 010 Feet From The South Feet F			
Check Appropriate Box to Indicate Nature of Notice	ce. Report, or Other Data		
11. Check Appropriate Box to indicate Nature of Notes	SUBSEQUENT REPORT OF:		
NOTICE OF INTENTION TO:			
	PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
IPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING	ND CEMENT JOB		
OTHER: Add perforations & acidize X OTHER:			
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed			
work) SEE RULE 1103.			
Propose to add perforations in the Canyon and acidize as follows:			
1. TOOH with pump and rods. Nipple up BOP and TOOH with tubing anchor and tubing.			
1. TOOH with pump and rods. Nipple up BOF and 100h with casts, 40 & 7742' (10 holes); 2. Perforate 7733-7829' w/32 holes as follows: 7733, 36, 38, 40 & 7742' (10 holes); 2. Perforate 7733-7829' w/32 holes as follows: 7706' (4 holes) and 7816, 18, 20,22, 27 & 7829'			
7762, 64 & 7766' (6 holes); //93 & //96 (4 holes) and /625, 25,			
(12 holes) (2 SPF).			
4. Straddle acidize perforations 7733-7766'. 5. Set RBP at 7810'± and pressure test RBP. Set packer at 7600'.			
5. Set RBP at 7810'± and pressure test RBI: Det packet at the			

I hereby certify that the information above is true and complete to the best of my knowledge and belief. Production Clerk SIGNATURE . TELEPHONE NO. 505/748-1471 Rusty Klein TYPE OR PRINT NAME

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM

TOOH with RBP and packer. Put well on pump.

Acidize perforations 7654-7796'.

DISTRICT II SUPERVISOR

FEB 2 0 1995

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY -